

# Specifications

## MODELS

CECPM-1C and CECPM-1H

### Cabinet Shell:

Modular polypropylene cabinet. Resists cracks, fading and yellowing. Color molded into cabinet to hide scrapes caused by rough usage. Cabinet is easily removed for access to interior components. Just unfasten four screws and slide cabinet off.

### Frame:

A heavy gauge galvanized steel frame provides added strength and support. The frame also permits easy removal of side panels for maintenance and refurbishment.

### Cold Water Reservoir:

Type 304 stainless steel. External copper refrigerant coil. Reservoir insulation is a removable polystyrene jacket. Temperature is controlled by adjustable thermostat.

### Refrigeration Unit:

Convection cooled condenser. Internally spring mounted, hermetically sealed compressor with automatic overload protector. No lubrication needed. Environmentally friendly R134a refrigerant is controlled by calibrated capillary tube.

### Capacity\*:

Cooler provides .7 G.P.H. (2.7 L.P.H.) of 50°F (10°C) water when room temperature and bottled water temperature is 90°F (32.2°C).

### Hot Tank (CECPM-1H Only):

Type 304 stainless steel. 500 Watt externally mounted band type heating element can be easily removed without draining the water from the cooler. Storage capacity is 1-1/2 quarts (1.4 liters).

### Hot Water Thermostat:

Automatic thermostat factory set at approximately 180°F - 190°F (82°C - 88°C). Hot tank is protected by a heat limiter in the event of a thermostat failure. A hot tank on/off switch located on the shelf is easily accessible from rear. An optional adjustable thermostat is also available at extra cost.

### Float System:

Dual mechanical float system controls water level in reservoir. Secondary safety float/valve mechanism activates in case of primary valve failure. Safety system has a manual reset feature.

### Electrical:

115 Volts, 60 Hz. Compressor HP: 1/20 full load. Amps: CECPM-1C 1.2; CECPM-1H 5.5. Removable three wire service cord and polarized plug furnished.

### Cooler Dimensions:

Height: 38.0 in. (96.5 cm.)  
Width: 12.4 in. (31.4 cm.)  
Depth: 14.8 in. (37.5 cm.)

### Net Weights (approx.):

CECPM-1C: 38 lbs. (17.2 kg.)  
CECPM-1H: 40.0 lbs. (18.1 kg.)

### Shipping Weights:

CECPM-1C: 42.0 lbs. (19.1 kg.)  
CECPM-1H: 44.0 lbs. (20.0 kg.)

### Shipping Dimensions:

Height: 39.0 in. (99.1 cm.)  
Width: 13.2 in. (33.5 cm.)  
Depth: 15.5 in. (39.4 cm.)

### Limited 5 Year Warranty:

(Continental limits of the United States and Canada): Five years on the sealed refrigeration system and most component parts. Detailed warranty certificate

### Export Models:

Models available to operate on 230V-50/60 Hz. or 220-240V-50Hz. Models available with DEMKO, NEMKO and CE approvals. (UL not applicable to export models).

### Export Warranty:

One year on the sealed refrigeration system and most component parts.

**All specifications subject to change without notice.**

**Warning: Source water must be potable.**



\* Capacities are at Standard Rating Conditions of 50°F (10°C) outlet water, 90°F (32.2°C) inlet water and 90°F (32.2°C) ambient air. Rated in accordance with ARI Standard 1010-02.  
UL Listed to U.S. and Canadian Safety Standards.